# Conservation and Management of Lakes with Special Reference to Dal Lake

#### Sabah UI Solim

J&K Lakes and Waterways Development Authority, Srinagar, J&K

15/04/2009 15:27

#### LAKE ANALYSIS

S (Strengths)

1. Varied utilities, 2. High water flow, 3. flushing's thereof, 4. macrophyte dominated, 5. three outflow channels

W (Weaknesses)

1. Urban locale, 2. shallow depth, 3. inlake population, 4. High catchment-lake ratio,

(Opportunities)

1. Water level manipulation and regulation,

(Threats)


2. additional water inputs (Sindh), 3. water sports (Jet skies) for circulation, 4. manure, 5. biogas and 6. electricity

1. Unplanned urbanization, 2. erratic rainfalls 3. extensive weeds – their recycling 4. Timely implementation of conservation measures

#### Intensive Weaknesses catchment management afforestation and measures 47% of Sewerage and catchment is sewage treatment barren (161 – storm water works km²) out of 337 km<sup>2</sup> Surrounding Catchment: population Lake ratio = 3.O lac >10 Rehabilitation Dal Lake In-lake Mean depth population = 1.0 m~1.0 lac (assumed) (very shallow) Water level Shortage of manipulation staffand regulation project cost swelled from

300 to 1100 cr

# Urban Locale





## **Threats**

- Unplanned urbanization
- Erratic rainfalls
- Excessive weeds their recycling and regeneration
- Population living inside the lake
- Timely completion of conservation measures inadequate staff



- Inadequate infrastructural facilities has been observed to be the biggest impediment in implementing the projects and meeting the deadlines)
- Administrative bottle-necks





2004 onwards: Grants under National Lake Conservation

Programme

October 1999: MoEF engaged Alternate

Hydro Energy centre (AHEC)
of IIT Roorkee for preparation

of Detailed Project Report.

December, 2002 DPR cleared by State Cabinet

and submitted to Government

of India.

September, 2005: Sanctioned by GOI for Rs.298.76 Cr

## Reasons of Deterioration (DPR-AHEC-IIT Roorkee)

- Reduction in volume by silting caused mainly due to catchment area degradation.
- Increased pollution because of the increasing number of lake dwellers and floating gardens, entry of untreated sewage and solid waste from the peripheral areas and from the hamlets and house boats and agricultural return flow from catchment into the lake.
- Reduction and clogging of water channels within the lake because of encroachments leading to reduce circulation.
- Reduction of fresh water inflow into the lake.
- Nutrient enrichment of the lake-water and sediment resulting in excessive weed growth and change in the bio-diversity in the lake.
- Data deficiency
- Institutional deficiency

## Interventions

Nutrient & Solid wastes Sewerage and Sewage treatment – Houseboat sanitation

- Solid Waste management
- · Catchment area treatment

Hydrolo gy

- · Opening up of blocked channels, Brari-Numbal Cut and Conduit
- · Additional water from Padshahi Canal
- · Diversion works on Teilbal Nallah & Improvement to Nallah Amir Khan

Enrichment

- Deweeding (Manual and Mechanical)
- Dredging
- · Additional water from streams to the lake

Encroad h- hment

Encroac • Enforcement

Public awarenes

- Public Awareness Programmes
- Documentaries

S

Shoreline development

Aesthetics

## Conservation & Management Plan

Rupees in lacs

(MoEF Approved Project)


S.No.	Components	DPR Cost	Expenditure ending 12/2009
1.	Sewerage Treatment Works	9691.38	4726.99
2.	Solid Waste Management	75.59	87.99
3.	Hydraulic Works	1283.03	601.87
4.	Restoration & Dev. Works	4961.79	2670.70
5.	Catchment Management Works	2584.00	1005.21
6.	Infrastructure facilities	1592.33	216.26
7.	Public Awareness	541.08	44.10
8.	Unforeseen Miscellaneous	435.85	343.71
9.	Provision for land acquisition	8710.00	
	under conservation component		4811.24
	Total	29875.74	14507. 97

# Financial Implications (Amount in crore)

S.No.	Component	Coot	Source of funding	
<b>3.NO.</b>	Component	Cost	Source of funding	
Part – I (Conservation)				
1.	Conservation and Mgt. Prog	298.76	MoEF, GOI under NLCP	
2.	Conservation and Mgt. Prog (Acq. of land/Structures within lake and dredging/procurement of lake cleaning machines	356.00*	PMPRP	
3.	Laterals/House Connectivity	55.00	State Plan (not provided in the NLCP norms)	
4.	Conservation of Brari-Numbal (incl. Aqc. of land)	27.00	State Plan	
	Sub Total	736.76		
Part – II Rehabilitation & Resettlement			State Plan/JNNURM -	
a) Rakhi Arth		402.00	HUPA, GOI	
G. Total		1138.76		

## **Physical Progress**

## **Conservation Plan**



## **Sewage Treatment Plants**

Total capacity to be installed = 36.7 MLD
Plants = 5 Nos

Plants Commissioned = 3 Nos (15.2 MLD)

#### STP Hazratbal (7.5 MLD)

Targeted Sewers lines = 7909 m

Sewer lines completed = 7652.50 m (%)

Targeted laterals = 20187 m

Laterals = 12557 m (%)

House Connectivity = 65%

> IPS = 2 (One commissioned and one to be Mar-2010)

#### STP Habak (3.2 MLD)

Targeted Sewers lines = 3057 m (100%)

Sewer lines completed = 3057 m
 Targeted laterals = 8163 m

Laterals = 7611 m (%)

► House Connectivity = 80%

#### STP Laam (4.5 MLD)


Targeted Sewers lines = 4920 m (100%)


Targeted laterals = 32620 m

Laterals = 24843 m (%)

House Connectivity = 90%

> IPS = 1 No. (Commissioned)





## Low Cost Sanitation (LCS)

 14 villages lack basic sanitation facilities around Dal Lake – Have constructed open latrines on inflowing Nallahs- like Telbal and Boutkul Nallahs

DPR for LCS


Sulabh International (Appointed by IIT Roorkee)

No. of households

**- 7150** 

• No. of community toilets

- 14



Map showing peripheral villages


Solid waste management


Outsourced to NGOs

> Services provided to 7450 dwelling units including houseboats inside the lake.

About 9000 Cubic Mtr. of solid waste collected annually and disposal through Srinagar Municipal Corporation.







## Hydraulic Works



Settling basin at Teilbal Nallah commissioned - designed for 80,000 tons/yr





## Additional water for dilution and flushing

- Provision of additional water of **2** Cumecs for dilution and flushing purpose i.e. 5.27 x 10<sup>6</sup> m<sup>3</sup> per month
- Will bring 26.3% increase in flushing rate per month
- Will dilute the high concentration of nutrients in the lake.

## Catchment Management

Main contributory Catchment


(6 water sheds with 12 micro water sheds 337 Sq. Km area in Dachigam, Dara – Danihama, lake body and peripherals draining towards lake).


- Interventions & achievements
- Gully plugging, anti-erosion, toe-crates and check dams in storm-water rivulets, trenching, pasture development, fencing, harvesting, etc to achieve:

• To meet the project completion time line:

 The afforestation and its allied works in the catchment area shall be jointly carried out by LWDA, forest, Soil Conservation and Wild Life Departments

### Structural measures





## Watershed Development Committees

- For participatory approach LDA has constituted watershed development committees.
- Participatory approach in:
  - Developmental activities
  - Active participation in the micro-action plan formulation
  - Maintenance and upkeep of assets

## Restoration & Development

## Restoration & Development

T = Mar- 2011 2 Reed Belt Control of non-Creation 1 point nutrient including inputs dredging = Mar-2011 T = Recurring Removing Dredging of accumulated Dredging & blocked channels Deweeding nutrients in the lake









# Impact of dredging

- ➤ Removal of 2.53 x 10<sup>6</sup> m³ of bottom sediments, thereby bringing and equivalent increase in volume of the lake
- > 40% increase in water transparency in Hazratbal Basin
- > 10% decrease in COD values in Hazratbal Basin.
- > 295.11 tons of nitrogen and 73.74 tons of phosphorus removed from lake nutrient budget as a consequence.







# Dredging of Blocked channels

Rainawari Navigational 2140 m Channel completed Nowpora Navigational 502 m Channel completed 1355 m Meerakshah feeding channel Completed 400 m Chowdiri Bagh channel completed 100 m Dalkawpora channel completed 135 m Chaku channel completed

Improved circulation

Three more blocked channels to be dredged this year - process completed

Total 38 blocked channels to be dredged by Mar- 2011




20,000 cum of wet weed on average is removed from Dal-Nagin lake area relieving the lake of nutrients trapped in weeds.



**Before Dweeding** 

**During Dweeding** 










## Removal of floating gardens at Nageen





**Before** 

**After** 

## Public Awareness



- •Public awareness program carried out regularly through electronic and print media, seminars, symposiums, debates and focused group discussions.
- Anti polythene campaign carried out with NGOs.
- Legislation passed by State Government banning use of nonbiodegradable material like plastics, polythene etc.
- Road show & public awareness prog. was recently held on Dec-1<sup>st</sup> 2008 in association with a educational institutions and traffic police.
- Technical offers received from various NGOs and firms for carrying out of the awareness drives and programmes round the year- evaluation under process for final allotment

# Infrastructure

• **Development of institutional infrastructure**Construction of 2 laboratories for monitoring lake-water quality and research work.

Equipment and machinery for the project

Dredgers 2 Nos.

Harvesters 4 Nos.

Motor Boats 4 Nos.

Excavator 1 No.

JCB Excavator//Loader 1 No.

Tippers 2 Nos.















Aquarius Truxor DM 4700 B2

Watermaster Classic-III








### Research and Development

 Research and Monitoring Wing set up for regular monitoring of lake water quality and lake flora and fauna.

• Scientific Advisory Committee Meeting held in June 2009- valuable suggestions obtained – like Creation of artificial wetlands in upstream of Telbal Nallah, Augmentation of treatment process of existing STPs, incineration of Azolla, low cost sanitation etc.









#### Eutrophication of the lakes in relation to Dal Lake With emphasis on

nutrient inputs Watershed, urbanization, land use, Conservation & Management geology, riparian developments, up **Increased** stream Reduced loading If increased loading stage 1 loading Low/natural continues input Dal Lake Reduced loading stage 2  $O_2$  pH, Temperature, OM, Sustainable Management  $NO_3-N$ 



### Areas of diffuse runoff



#### Water budget (annual)

• Inflow (x 10<sup>6</sup> m<sup>3</sup>)

> Streams = 248.3

**>** Runoff = 43.8

> Sewage = 6.6

> Treated Sewage = 2.5 + 3.1\*

> Precipitation = 9.14

► Ground water = 10.0

Outflow (Mcm)

> Exit gates = 274.5

► Evaporation = 14.8

Drinking water = 25.92

> Irrigation = 0.54

• Lake Volume (Mcm)

> Volume

Volume added by dredging

> Total volume

• Flushing rate and water loading

> Flushing rate

(Telbal, Boutkul Meerakshah, and Pishpuw
(Lake Hill side, Srinagar Center, S. North)
(Mainly from old city areas)
(STPs Hazratbal, Habak, and Laam. \* Diverted
after treatment at Brari-Numbal STP to River Jehlum)
(Lake surface)
(Interpolated from inflows-outflows and storage change)


(Dal Exit, Nallah Amir Khan, and Brari Numbal) (Natural) (Nishat and Pokribal plants of PHE department) (Royal Springs Golf Course)

= 16.0

= **2.65** (16.5% of actual lake vol.)

= 18.6

= 14.5 (time per year)




## ➤ Telbal-Dachigham Watershed P loading

- P conc. 2000 & 2007 (*p*>0.05), P conc. vs. discharge *p*>0.05
- P load 2000 = 59.1 tons
- P load 2007 = 119.6 tons

Two fold increase

*P*<0.05




## Urbanized catchments (S.C, S.N & LHS)

- P conc. 2000 & 2007 (*p*>0.05)
- P load 2000 = 5.4 tons
- P load 2007 = 67 tons

Manifold increase

*P*<0.05




### Watershed Measures Adopted & Flaws

- ✓ Measures adopted
- Re-forestation
- Gully plugging, check dams, gabion check dams, and control of stream bank erosion by installing crate networks
- Urbanized catchments inhabiting a three lack people lack storm water runoff facilities and treatment- directly enters the lake
- > Flaws
- 140 km² of Telbal-Dachigham catchment is barren landscape, which has not been touched
- Overgrazing continues
- Use of phosphate fertilizers continues
- Conversion of forested land for agriculture continues
- Pace of urbanization is quite rapid

## Over the period of time the lake appears to be losing its capacity as a sink for P.


- ✓ Phosphorus retention in 1981-82 = 33% (Ishaq & Kaul (1990)
- ✓ Phosphorus retention in 2000 = 27%
- ✓ Phosphorus retention in 2007 = 22%
- P retention in the lake has decreased progressively.
- This clearly shows that the lake has by and largely lost the efficacy of P trapping.
- Historic anthropogenic pressures have left enough P reserves in the bottom sediments, which over time have started to get released, such that the lake is in the stage of transition from P-trapping to p-releasing.
- Gross internal P release rate are high = 20.6 mg m<sup>-2</sup> day<sup>-1</sup>

### Nitrogen Budget



The nitrogen budget shows that a high percentage of the total nitrogen input is lost to sinks. The net sinks i.e. loss through uptake, atmospheric exchanges and also to some extent to sediments are a much more important elimination routes than outflow losses.


#### NO<sub>3</sub>-N balance




During spring-summer period, 78 - 92% of NO<sub>3</sub>-N load (9.1 g m-2 yr-1 i.e. 52.6% of total yearly loading) is either entrapped within the newly developing macrophyte tissues, or appears to get eliminated by virtue of temperature controlled microbial denitrification.

#### Influence of NO<sub>3</sub>-N on internal P release


- ►Low levels of NO<sub>3</sub>-N in the lake waters have been shown to influence the sediment P release (Ripl 1976; Andersen 1982; Boström *et al.* 1982; Jensen & Andersen 1992; Søndergaard *et al.* 2000). According to Boström *et al.* (1988) no P release seems to occur at a NO3-N supply of > 0.5 mg m<sup>-2</sup> h<sup>-1</sup>, while Andersen (1982) had reported P release in shallow polymictic Danish Lakes with NO<sub>3</sub>-N < 500 μg l-1
- **√NO<sub>3</sub>-N supply in Dal Lake is much** higher in magnitude of 0.5 mg m<sup>-2</sup> h<sup>-1</sup>
- √Low NO<sub>3</sub>-N of <500 μg l<sup>-1</sup> during spring-summer periods result from denitrification and entrapment within macrophytes.
- ✓ concurrent occurrence of NO<sub>3</sub>-N minima and P maxima, and viceversa observed in the lake.
- ✓In relation to NO<sub>3</sub>-N minima, P maxima were observed during May, July, and September.




#### Within lake interventions in relation to eutrophic status of the



"FEED BACK" LOOP: Linking macrophyte nutrient and organic demands to nutrient and organic inputs from macrophyte decomposition and translocation, and dissolution from bottom sediments and translocation (*c.f.* Landers 1982; Engel 1988; Barko *et al.* 1991). Removal of ~ 20% of the standing macrophyte biomass from the lake still leaves a huge proportion in the lake to augment the enrichment of the bottom sediments with N, P and TOC, which in turn bring increase in biomass and regeneration potential through a feed back loop





Critical load tolerance range = 0.1 - 0.2 g m<sup>-2</sup> yr<sup>-1</sup>

• As the lake is gradually loosing the P trapping capacity, it is expected, that if significant reduction is not brought in external loadings, the internal loading with increase with time, which will further augment total P loading and the lake P concentrations.

# Decisions of 2<sup>nd</sup> Scientific Advisory Committee

- Creation of artificial wetlands up-stream of the main feeding stream i.e. Telbal Nallah
- Creation of buffer zones along the eastern shores to sponge the diffuse runoff
- With this decision both point and non-point sources of pollution for the lake will be tackled



### Regulatory standards and indices

- Lack of regulatory norms for discharge into the lakes the present CPCB standards are for discharge of COD, BOD, TSS into the inland water bodies. The definition of inland water bodies applies to wide range of water bodies including rivers and wetlands which have higher assimilative capacities as in comparison to lakes
- There are no standards for discharge of nitrogen and phosphorus into the lakes and rivers, which in addition to COD and BOD are the critical parameters of eutrophication
- Four categories A, B C and D type waters are classified primarily from drinking water point of view and not from eutrophication control.
- Lack of sanitary code or procedure
- Inspirations can be drawn from European water framework directive which encompasses both chemical and biological indices.

### Thank You